



### Phonak Cassia 10 Petite (M)


Small ITE, battery size 10A (for fitting range, product details and available options, please see Product Information or visit [www.phonakpro.com](http://www.phonakpro.com)).

Petite devices do not have wireless functionality. Unless otherwise specified, all data obtained are measured with 5 mm tubing and Phonak Target measurement settings.


#### Ear simulator data

EN / IEC 60118 and IEC 60711

#### Output sound pressure level



#### Acoustic gain



Frequency range	<100 Hz - 8200 Hz		
Total harmonic distortion	500 Hz	800 Hz	1600 Hz
	2.5%	2.5%	2%
Battery current	Quiescent	Working	
	1.1 mA	1.2 mA	
Equivalent input noise level	19 dB SPL		

#### Dynamic data


Compression	Attack time	Recovery time
	10 ms	50 ms

Note: Using pure tone measurements with a digital hearing instrument can result in a wavy frequency response. This is an artifact resulting from the use of a narrowband input signal and does not effect the actual performance with naturally occurring broadband input signals.


#### 2cm<sup>3</sup> coupler data

ANSI S3.22-2003

#### Output sound pressure level



#### Acoustic gain




Frequency range	<100 Hz - 7900 Hz		
Total harmonic distortion	500 Hz	800 Hz	1600 Hz
	1.5%	1.5%	1%
Equivalent input noise level	19 dB SPL		

#### Dynamic data

Compression	Attack time	Recovery time
	10 ms	50 ms

#### Input / Output characteristics at 2000 Hz




# Phonak Cassia 10 Petite (P)


## Ear simulator data

EN / IEC 60118 and IEC 60711

### Output sound pressure level



### Acoustic gain



Frequency range	<100 Hz - 7500 Hz		
Total harmonic distortion	500 Hz	800 Hz	1600 Hz
	2.5%	2.5%	2%
Battery current	Quiescent	Working	
	1.1 mA	1.2 mA	
Equivalent input noise level	19 dB SPL		


### Dynamic data

Compression	Attack time	Recovery time
	10 ms	50 ms


## 2cm<sup>3</sup> coupler data

ANSI S3.22-2003

### Output sound pressure level



### Acoustic gain




Frequency range	<100 Hz - 7200 Hz		
Total harmonic distortion	500 Hz	800 Hz	1600 Hz
	1.5%	1.5%	1.5%
Equivalent input noise level	19 dB SPL		

### Dynamic data

Compression	Attack time	Recovery time
	10 ms	50 ms

### Input / Output characteristics at 2000 Hz



## Technical Data


# Phonak Cassia 10 Petite (SP)

(available in specific countries only)


### Ear simulator data

EN / IEC 60118 and IEC 60711

#### Output sound pressure level



#### Acoustic gain



Frequency range	< 100 Hz - 7500 Hz		
Total harmonic distortion	500 Hz	800 Hz	1600 Hz
	1.5%	1.5%	1%
Battery current	Quiescent	Working	
	1.1 mA	1.2 mA	
Equivalent input noise level	19 dB SPL		


#### Dynamic data

Compression	Attack time	Recovery time
	10 ms	50 ms


### 2cm<sup>3</sup> coupler data

ANSI S3.22-2003

#### Output sound pressure level



#### Acoustic gain




Frequency range	< 100 Hz - 7200 Hz		
Total harmonic distortion	500 Hz	800 Hz	1600 Hz
	1%	1%	1%
Equivalent input noise level	19 dB SPL		

#### Dynamic data

Compression	Attack time	Recovery time
	10 ms	50 ms

#### Input / Output characteristics at 2000 Hz



**PHONAK**