

Milo micro


Technical Data



Ear simulator data

EN / IEC 60118 and IEC 60711

Output sound pressure level




Small moderate power microBTE, battery size 13 and omni directional microphone (for fitting range, product details, and available options, please see "Milo Product Information" or visit www.phonak.com).

Unless otherwise specified, all data obtained are measured with the hook HE9 680 and iPGF measurement settings.


Note: Measurements with pure tones of a digital hearing instrument can result in a wavy frequency response. This is an artifact resulting from the use of a narrowband input signal and does not reflect the actual performance with naturally occurring broadband input signals.

Acoustic gain



Frequency range (DIN 45605)	<700 Hz - 6200 Hz		
Total harmonic distortion	500 Hz	800 Hz	1600 Hz
	2.0%	2.5%	1.0%
Battery current	Quiescent	Working	
	1.0 mA	1.1 mA	
Equivalent input noise level	22 dB SPL		

Induction coil sensitivity




Dynamic data

Compression	Attack time	Recovery time
	1 ms	50 ms


2cm³ coupler data

ANSI S3.22-2003


Output sound pressure level



Input / Output characteristics at 2000 Hz




Acoustic gain



Frequency range (DIN 45605)	<100 Hz – 6200 Hz		
Total harmonic distortion	500 Hz	800 Hz	1600 Hz
	2.0%	2.0%	1.0%
Equivalent input noise level	22 dB SPL		

Induction coil sensitivity



Dynamic data

Compression	Attack time	Recovery time
	1 ms	50 ms