
Government Services

Phonak Belong™ RIC Digital Hearing Aids and CROS (36C79119D0036)





Customer Information

Pay	er:			PO #:					
	ROES (DALC PH5120018	8626)		Contact Name:					
	Other			Phone Number:					
	RACHAP (Enclose payr	ment and if paying by cc, RACH.	AP authorization form)	Email Address:					
Ship	To:			Patient's Last Name:					
Add	ress:			Patient's 4 Digit SSN:					
City	·:	State:	Zip:	Age:	Gender:				
] [] 	Phonak Naida B90 Charging Case [07 Mini Charger [075- Power Pack [071-0	D-R RIC [050-0437-xx]	R Phonak Audéo B90■ Charging Case [07□ Mini Charger [075-□ Power Pack [071-00	5-0111-11] -0112-11]	□ R Phonak Audéo B90-312T [050-0357-xx]□ R Phonak Audéo B90-13 [050-0361-xx]				
•			☐ Champagne (P5)	☐ Graphite Gray (P7) ☐ Alpine White (T7)					
	☐ Sand Beige (P1) ☐ Chestnut (P4)		☐ Silver Gray (P6)	☐ Velvet Black (P8)					
Ste	p 3: Select Receiv	ver (one per side)							
	STANDARD) R 0 [054-0102/0103] R 1 [054-0104/0105] R 2 [054-0106/0107] R 3 [054-0108/0109]	xP (P L R L R L R L R	1 [054-0237/0238] 2 [054-0239/0240]		XUP (ULTRA POWER) Hard cShell only. L R 0 L R 1 L R 2 L R 3				

Step 4: Select Coupling - Please select options from A, B or C for each aid

A. cShell				B. SlimTip xS and xP only			C. Smokey Domes		
SHELL COLOR RETENT			ON	Material		Venting		OPEN DOMES	
L R	Pink [26]	L R	Soft Coat [SC]	LR	Hard Acrylic	L R	Cavity [Y3L]	only avo	nilable with xS
L R	Tan [14]	L R	Canal Lock [CL]*	LR	Soft Silicone		N/A on soft silicone	L R	Small [054-0704]
L R	Cocoa [22]	L R	Skeleton Lock [SL]*	Color		LR	AOV [AOV]	L R	Medium [054-0705]
L R	Brown [28]	VENTING	3		Clear	LR	Large Vent [S30]	L R	Large [054-0706]
L R	Clear [21]	L R	AOV[AOV]	Wax Prevention		LR	Medium [S25]	CLOSED	Domes
L R	Red [R]	L R	Custom Large Vent [D_3L]	Space & size permitting N/A on soft silicone		LR	Small [S20]	availabl	e with xS or xP
L R	Blue [B]	L R	Semi-IROS [IA30]			LR	Pressure [S12]	L R	Small [054-0707]
FACEPLATE COLOR		L R	Large [S30]	LR	Wax Trap [CS]	LR	No Vent [X]	L R	Medium [054-0708]
L R	Pink [26]	L R	Medium [S25]		N/A with other wax option	RETENTIO	RETENTION		Large [054-0709]
L R	.] R Tan [14]		Small [S20]	■ Extended Receiver	LR	Canal Lock [CL]	Power	<u>Domes</u>	
L R	Cocoa [22]	L R	Pressure [S12]		Tubing [ER]		Cavity vent only	available	e with xS or xP
L R	Brown [28]	L R	No Vent [X]	LR	Do Not Add Wax	LR	Barber Pole [RR]	L R	Small [054-0710]
<u>Options</u>		Wax P	REVENTION	LR	Protection [X]	LR	Softcoat [SC]	L R	Medium [054-0711]
L R	Cut as marked [R.]	L R	Wax Trap [CS]				N/A on soft	LR	Large [054-0712]
L R	Canal Bell [BC]	L R	Ext Receiver Tubing [ER]*			LR	Skeleton Lock [SL]		
■ R No Removal Line		■ Spring Wax Guard [WS]				LR	Use Scan on File	Please Note: Default Options	
■ Use Scan on File		L R	No Wax Protection					are itali	cized.

*Clear, Pink, Cocoa, Tan & Brown shells only Warranties including L/D do not

apply on SlimTip

Step 5: Wil	reless Accessories								
	ak PilotOne II [076-0019-P500070] ak ComPilot Air II [054-0722]	L R	Phonak ComPilot Phonak RemoteN	II [054-0721] Mic [076-0039-P500070]		R TVLink	II [076-0040-P511070]		
Step 6: Sel	ect Phonak CROS B Transmit	tter for <i>i</i>	Audéo B (unaid	able ear)					
Specify Side	Transmitter		Color	Retention					
L R	Phonak CROS B-R [050-0601 Beige (Std.) (01), Sand Beige (P1), Sandah Chestnut (P4), Champagne (P5), Silver G Graphite Gray (P7), Velvet Black (P8), Alp	wood (P3), ray (P6),		Select Tube/V □ 0 [054-06	be and Dome (default) Vire Length (0–3): 90/054-0686]				
	*Compatible with Audéo B90-R only								
L R	Phonak CROS B-312 [050-02] Beige (Std.) (01), Sand Beige (P1), Sanda Chestnut (P4), Champagne (P5), Silver (Graphite Gray (P7), Velvet Black (P8), A.		7)	☐ CROSTip [06	OR CROSTip [062–0025–01] New impression sent Use scan on file#:				
Step 7: Aug	Phonak CROS B-13 [050-027: Beige (Std.) (01), Sand Beige (P1), Sandah Chestnut (P4), Champagne (P5), Silver Gi Graphite Gray (P7), Velvet Black (P8), Alp	wood (P3), ray (P6), sine White (T	7)			61] (included	d with Phonak CROS B-13)		
Audiometric In	NFORMATION_	Preprog	RAMMING OPTIONS						
	ith all preprogramming requests. Hz for AOV Venting 500 1000 2000 3000 4000		L R NAL NL1 Fitting Formula [FIT03] L R Add Speech in Loud Noise Program [STZP0] L R Add Speech in 360° [ZMCPo]			NAL NL2 F Change pu Add Roger Add Speec Add Tinnit	Block on [WHB23] 2 Fitting Formula [FIT04] 2 push button to VC [PBB02] 3 ger/DAI+Mic Program [FMMP0] 4 eech in Wind Program 5 nitus Balance Program [TPMP0] 6 oustic DuoPhone Program		
Step 8: Not	tes								

